### **Product information**

## Coolant Ready Mix RAF 11



#### **Description**

Coolant Ready Mix RAF11 is a ready-to-use mixture based on ethylene glycol. The antifreeze contains no amines, nitrites or phosphates and offers ideal protection from frost, rust and overheating through its special inhibitor formulation. This therefore provides reliable vehicle performance all year round.

#### LIQUI MOLY recommends this radiator antifreeze for vehicles that require a product with the following following manufacturers' approvals:

Behr

BMW GS 94000 CUMMINS 85T8-2

MB 325.0 MB 325.2

Alfa Romeo 9.55523 Chrysler MS-7170 Fiat 9.55523 Lanca 9.55523

Iveco Standard 18-1830 Volvo Cars 128 6083 / 002 Opel/GM GME L1301 Saab 6901 599

Saturn

JI Case JIC-501

Lada TTM VAZ 1.97.717-97

MAN 324 Type NF **MTU MTL 5048** 

Perkins

Porsche TL-774 C

**Toyota Motor Corporation** 

Volvo Construction 128 6083 / 002

Volvo Trucks 128 6083 / 002

VW specification G11

Audi TL-774 C

Seat TL-774 C

Skoda TL-774 C

VW TL-774 C

as well as for vehicles that require a radiator antifreeze of this quality.

#### **Properties**

- prevents operational malfunctions
- contains no amines, nitrites or phosphates
- ready for use
- outstanding corrosion protection
- provides outstanding protection against overheating
- prevents the cooling system from freezing up
- for extended change intervals (note manufacturer's instructions)



#### **Technical data**

-20 bis +104 / -20 to +104 Frost and overheating °C

protection

Base Ethylenglykol mit

> Inhibitoren / ethylene glycol with inhibitors

Density at 20 °C 1,05 g/cm<sup>3</sup> Color / appearance blau / blue Flash point > 100 °C Shelf life in original sealed 60 months

container

#### Areas of application

Suitable for all cooling systems and engines (including aluminium engines) in passenger vehicles, commercial motor vehicles, buses, agricultural machinery and stationary engines/machines where coolant system protection of this quality is required.

#### **Application**

Clean the coolant system with LIQUI MOLY Radiator Cleaner (item no. 3320). Empty the coolant system, rinse thoroughly with water and fill with Coolant Ready Mix RAF11. Disposal is made according to the local regulations. The change intervals vary according to the manufacturer's instructions. Coolant Ready Mix RAF11 is mixable and compatible with radiator antifreeze containing silicates according to VW standard G11 - TL 774-C (LIQUI MOLY Radiator Antifreeze RAF11) or original silicate-free radiator antifreeze according to VW standard TL 774-D/F (LIQUI MOLY Radiator Antifreeze RAF12 Plus or LIQUI MOLY Coolant Ready Mix RAF12 Plus).

#### Available pack sizes

1 l Bottle plastic 20660

D-GB-I-E-P

5 l Canister plastic 8809

D-GB-I-E-P

8822 20 l Canister plastic

D-GB

# **Product information**

### PI 14/12/01/2018



# Coolant Ready Mix RAF 11

Available pack sizes

200 l Drum sheet metal 8823

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-13 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de