

Page 1 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

TRAKTOROEL UTTO SAE 10W30 20 L

Art.: 4749

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

(GB)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains C14-18 alpha-olefin epoxide, reaction products with boric acid. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients



Page 2 of 11

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

3.1 Substance

n.a. 3.2 Mixture

Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	-
CAS	
content %	10-<40
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
zing bis[0 0-bis/2-otby/boxy/]] bis(dithionbosphato)	Substance with specific cone limit(s) acc. to PEACh-

zinc bis[0,0-bis(2-ethylhexyl)] bis(dithiophosphate)	registration
Registration number (REACH)	01-2119493635-27-XXXX
Index	
EINECS, ELINCS, NLP	224-235-5
CAS	4259-15-8
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318
	Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Give moderate amounts of water to drink.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Drying of the skin. Irritation of the skin.

Initation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures



Page 3 of 11

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

5.1 Extinguishing media

Suitable extinguishing media

CO2 Foam Dry extinguisher Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Oxides of sulphur Flammable vapour/air mixtures

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation, and contact with eyes or skin. Do not carry cleaning cloths soaked in product in trouser pockets. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.

Ensure good ventilation.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Do not heat to temperatures close to flash point.

Take measures against electrostatic charging, if appropriate.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 4 of 11

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Protect against moisture and store closed.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral	Content	t %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)		
Monitoring procedures:	 Draeger - Oil 10/a-P (67 28 371) 		
	- Draeger - Oil Mist 1/a (67 33 031)		
BMGV:	Other information:		
Chemical Name	Baseoil - unspecified	Content	t %:
WEL-TWA: 300 mg/m3 (AGW)	WEL-STEL: 2(II) (AGW)		
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581)		
	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 		
	- Compur - KITA-187 S (551 174)		
BMGV:	Other information:		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	0,14	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,42	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,09	mg/cm2	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,42	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	9,59	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,21	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,09	mg/cm2	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,07	mg/m3	
• •	Environment - freshwater		PNEC	0,004	mg/l	
	Environment - sediment, freshwater		PNEC	0,0701	mg/kg	
	Environment - marine		PNEC	0,0046	mg/l	
	Environment - sediment, marine		PNEC	0,00701	mg/kg	
	Environment - soil		PNEC	0,0548	mg/kg	
	Environment - air		PNEC	7,1	mg/m3	
	Environment - sewage treatment plant		PNEC	3,8	mg/l	

8.2 Exposure controls

8.2.1 Appropriate engineering controls



Page 5 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection: Protective nitrile gloves (EN 374) Minimum layer thickness in mm: 0,35 Permeation time (penetration time) in minutes: >= 480 Protective PVC gloves (EN 374) Protective hand cream recommended. The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

(GB)

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow, Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	36 °C
Initial boiling point and boiling range:	Not determined
Flash point:	230 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined



Page 6 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Explosive properties: Oxidising properties:

(GB)

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content: Not determined Not determined 0,885 g/ml Not determined Insoluble Not determined Not determined 9,5 mm2/s (100°C) 55 mm2/s (40°C) Not determined Not determined

Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Protect from humidity. Open flame, ignition sources **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification). TRAKTOROEL UTTO SAE 10W30 20 L

Toxicity / effect	Endpoin t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.



Page 7 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

B

Toxicity / effect	Endpoin t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>3100	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	30	mg/kg	Rat	OECD 421 (Reproduction/Develop mental Toxicity Screening Test)	
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	125	mg/kg		OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	

SECTION 12: Ecological information

rt.: 4749		-					
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:					-		n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and							Isolate as much as
degradability:							possible with an oil
0							separator.
Bioaccumulative							n.d.a.
potential:							
Mobility in soil:							n.d.a.
Results of PBT and							n.d.a.
vPvB assessment							
Other adverse effects:							n.d.a.

zinc bis[0,0-bis(2-eth	ylhexyl)] bis(dit	hiophosp	hate)				
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	4,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EC50	48h	75	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to algae:	ErC50	72h	>240	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	



Page 8 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

Persistence and degradability:			<5	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	
Bioaccumulative potential:	Log Pow		3,6				
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	16h	380	mg/l	Pseudomonas putida	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

(GB)

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements	
UN number:	n.a.
Transport by road/by rail (ADR/RID)	
UN proper shipping name:	
Transport hazard class(es):	n.a.
Packing group:	n.a.
Classification code:	n.a.
LQ (ADR 2015):	n.a.
Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
UN proper shipping name:	
Transport hazard class(es):	n.a.
Packing group:	n.a.
Marine Pollutant:	n.a
Environmental hazards:	



Page 9 of 11

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749

Transport by air (IATA)

UN proper shipping name: Transport hazard class(es): Packing group: Environmental hazards:

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

For classification and labelling see Section 2.

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable. Directive 2010/75/EU (VOC): < < 0,1 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1 - 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H304 May be fatal if swallowed and enters airways. H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard Eye Dam. — Serious eye damage Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

AC Article Categories acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATE Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA BCF **Bioconcentration factor** Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BGV

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

n.a. n.a. Not applicable



Page 10 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749 BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand Bromine Science and Environmental Forum BSEF body weight bw **Chemical Abstracts Service** CAS CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dw drv weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency EEA European Economic Area EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms United States Environmental Protection Agency (United States of America) EPA ERC **Environmental Release Categories** Exposure scenario ES etc. et cetera EU **European Union** EWC European Waste Catalogue Fax. Fax number general aen. GHS Globally Harmonized System of Classification and Labelling of Chemicals Global warming potential GWP Hen's Egg Test - Chorionallantoic Membrane HET-CAM HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer International Air Transport Association IATA Intermediate Bulk Container IBC IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform ChemicaL Information Database LC lethal concentration LC50 lethal concentration 50 percent kill lowest published lethal concentration LCLo Lethal Dose of a chemical 1 D LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) NOAEC No Observed Adverse Effective Concentration

(GB)



(GB) Page 11 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.08.2015 / 0012 Replacing version dated / version: 14.07.2015 / 0011 Valid from: 21.08.2015 PDF print date: 27.08.2015 TRAKTOROEL UTTO SAE 10W30 20 L Art.: 4749 NOAFL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level **Ozone Depletion Potential** ODP OECD Organisation for Economic Co-operation and Development organic org. PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic Chemical product category PC ΡE Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential parts per million ppm PROC Process category PTFE Polytetrafluorethylene REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature SAR Structure Activity Relationship Sector of use SU SVHC Substances of Very High Concern Telephone Tel. ThOD Theoretical oxygen demand Total organic carbon TOC TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) United Nations Recommendations on the Transport of Dangerous Goods UN RTDG VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.